

Package ‘ROpenFLUID’

July 7, 2016

Type Package

Title Package for using OpenFLUID within the GNU R environment

Version 2.1.2-20160428

Date 2016-07-07

Author Jean-Christophe Fabre <fabrejc@supagro.inra.fr>

Maintainer Jean-Christophe Fabre <fabrejc@supagro.inra.fr>

Description ROpenFLUID is a collection of functions to load, parameterize, run and analyze OpenFLUID simulations within the GNU R environment.

URL <http://www.openfluid-project.org>

License GPL-3 + file LICENSE

Depends R (>= 2.6.2)

Suggests RUnit

LazyLoad yes

RoxygenNote 5.0.1

R topics documented:

| | |
|---|----|
| OpenFLUID.addExtraObserversPaths | 1 |
| OpenFLUID.addExtraSimulatorsPaths | 2 |
| OpenFLUID.addVariablesExportAsCSV | 3 |
| OpenFLUID.createAttribute | 3 |
| OpenFLUID.getAttribute | 4 |
| OpenFLUID.getDefaultDeltaT | 5 |
| OpenFLUID.getExtraObserversPaths | 6 |
| OpenFLUID.getExtraSimulatorsPaths | 6 |
| OpenFLUID.getGeneratorParam | 7 |
| OpenFLUID.getModelGlobalParam | 8 |
| OpenFLUID.getObserverParam | 8 |
| OpenFLUID.getObserversPaths | 9 |
| OpenFLUID.getPeriodBeginDate | 10 |
| OpenFLUID.getPeriodEndDate | 11 |

| | |
|---|----|
| OpenFLUID.getSimulatorParam | 11 |
| OpenFLUID.getSimulatorsPaths | 12 |
| OpenFLUID.getUnitsClasses | 13 |
| OpenFLUID.getUnitsIDs | 14 |
| OpenFLUID.getVersion | 14 |
| OpenFLUID.loadResult | 15 |
| OpenFLUID.loadResultFile | 16 |
| OpenFLUID.openDataset | 16 |
| OpenFLUID.openProject | 17 |
| OpenFLUID.printSimulationInfo | 18 |
| OpenFLUID.removeAttribute | 18 |
| OpenFLUID.removeModelGlobalParam | 19 |
| OpenFLUID.removeObserverParam | 20 |
| OpenFLUID.removeSimulatorParam | 20 |
| OpenFLUID.resetExtraObserversPaths | 21 |
| OpenFLUID.resetExtraSimulatorsPaths | 22 |
| OpenFLUID.runProject | 22 |
| OpenFLUID.runSimulation | 23 |
| OpenFLUID.setAttribute | 24 |
| OpenFLUID.setCurrentOutputDir | 25 |
| OpenFLUID.setDefaultDeltaT | 25 |
| OpenFLUID.setGeneratorParam | 26 |
| OpenFLUID.setModelGlobalParam | 27 |
| OpenFLUID.setObserverParam | 27 |
| OpenFLUID.setPeriodBeginDate | 28 |
| OpenFLUID.setPeriodEndDate | 29 |
| OpenFLUID.setSimulatorParam | 30 |
| ROpenFLUID | 30 |

OpenFLUID.addExtraObserversPaths

Adds paths to search for observers

Description

Adds paths to search for observers

Usage

OpenFLUID.addExtraObserversPaths (paths)

Arguments

paths the colon separated paths to add

See Also

OpenFLUID.getObserversPaths
OpenFLUID.getExtraObserversPaths
OpenFLUID.resetExtraObserversPaths

OpenFLUID.addExtraSimulatorsPaths
Adds paths to search for simulators

Description

Adds paths to search for simulators

Usage

```
OpenFLUID.addExtraSimulatorsPaths (paths)
```

Arguments

paths the colon separated paths to add

See Also

OpenFLUID.getSimulatorsPaths
OpenFLUID.getExtraSimulatorsPaths
OpenFLUID.resetExtraSimulatorsPaths

Examples

```
## Not run:  
OpenFLUID.addExtraSimulatorsPaths("/first/path/to/add")  
OpenFLUID.addExtraSimulatorsPaths("/second/path/to/add:/third/path/to/add")  
  
## End(Not run)
```

```
OpenFLUID.addVariablesExportAsCSV
```

Adds export of simulation variables as CSV files for a given units class

Description

Adds export of simulation variables as CSV files for a given units class

Usage

```
OpenFLUID.addVariablesExportAsCSV(ofblob, unitclass)
```

Arguments

| | |
|-----------|--|
| ofblob | the simulation definition blob |
| unitclass | the units class to add for simulation variables export |

See Also

```
OpenFLUID.loadResult
```

Examples

```
## Not run:
OpenFLUID.addVariablesExportAsCSV("TU")
OpenFLUID.addVariablesExportAsCSV("RS")

## End(Not run)
```

```
OpenFLUID.createAttribute
```

Creates an attribute for all spatial units of a class, initialized with a default value

Description

Creates an attribute for all spatial units of a class, initialized with a default value

Usage

```
OpenFLUID.createAttribute(ofblob, unitclass, attrname, attrval)
```

Arguments

| | |
|-----------|--|
| ofblob | the simulation definition blob |
| unitclass | the unit class |
| attrname | the attribute name |
| attrval | the default attribute value for alla units |

See Also

OpenFLUID.getAttribute
 OpenFLUID.setAttribute
 OpenFLUID.removeAttribute

Examples

```
## Not run:
OpenFLUID.createAttribute(ofsim, "SU", "area", 1.0)
OpenFLUID.createAttribute(ofsim, "SU", "code", "NONE")

## End(Not run)
```

OpenFLUID.getAttribute

Returns an attribute value for a given spatial unit

Description

Returns an attribute value for a given spatial unit

Usage

```
OpenFLUID.getAttribute(ofblob, unitclass, unitid, attrname)
```

Arguments

| | |
|-----------|--------------------------------|
| ofblob | the simulation definition blob |
| unitclass | the unit class |
| unitid | the unit ID |
| attrname | the name of the attribute |

Value

the attribute value

See Also

```
OpenFLUID.createAttribute  
OpenFLUID.setAttribute  
OpenFLUID.removeAttribute
```

Examples

```
## Not run:  
val = OpenFLUID.getAttribute(ofsim, "SU", 18, "length")  
  
## End(Not run)
```

```
OpenFLUID.getDefaultDeltaT
```

Returns the simulation time step

Description

Returns the simulation time step

Usage

```
OpenFLUID.getDefaultDeltaT(ofblob)
```

Arguments

ofblob the simulation definition blob

Value

the time step value in seconds

See Also

```
OpenFLUID.setDefaultDeltaT
```

Examples

```
## Not run:  
deltat = OpenFLUID.getDefaultDeltaT(ofsim)  
  
## End(Not run)
```

```
OpenFLUID.getExtraObserversPaths
```

Returns the added paths to search for observers

Description

Returns the added paths to search for observers

Usage

```
OpenFLUID.getExtraObserversPaths()
```

Value

a vector of paths

See Also

```
OpenFLUID.addExtraObserversPaths  
OpenFLUID.getObserversPaths  
OpenFLUID.resetExtraObserversPaths
```

Examples

```
## Not run:  
paths = OpenFLUID.getExtraObserversPaths()  
  
## End(Not run)
```

```
OpenFLUID.getExtraSimulatorsPaths
```

Returns the added paths to search for simulators

Description

Returns the added paths to search for simulators

Usage

```
OpenFLUID.getExtraSimulatorsPaths()
```

Value

a vector of paths

See Also

```
OpenFLUID.addExtraSimulatorsPaths
OpenFLUID.getSimulatorsPaths
OpenFLUID.resetExtraSimulatorsPaths
```

Examples

```
## Not run:
paths = OpenFLUID.getExtraSimulatorsPaths()

## End(Not run)
```

```
OpenFLUID.getGeneratorParam
```

Returns a generator parameter value

Description

Returns a generator parameter value

Usage

```
OpenFLUID.getGeneratorParam(ofblob, unitclass, varname, paramname)
```

Arguments

| | |
|-----------|---|
| ofblob | the simulation definition blob |
| unitclass | the unit class to which the generator is applied |
| varname | the variable name to which the generator is applied |
| paramname | the name of the parameter |

Value

the parameter value

See Also

```
OpenFLUID.setGeneratorParam
```

Examples

```
## Not run:
val = OpenFLUID.getGeneratorParam(ofsim, "SU", "var.flux", "fixedvalue")

## End(Not run)
```

```
OpenFLUID.getModelGlobalParam
```

Returns a model global parameter value

Description

Returns a model global parameter value

Usage

```
OpenFLUID.getModelGlobalParam(ofblob, paramname)
```

Arguments

| | |
|-----------|--------------------------------|
| ofblob | the simulation definition blob |
| paramname | the name of the parameter |

Value

the parameter value

See Also

```
OpenFLUID.setModelGlobalParam  
OpenFLUID.removeModelGlobalParam
```

Examples

```
## Not run:  
val = OpenFLUID.getModelGlobalParam(ofsim, "gvalue")  
  
## End(Not run)
```

```
OpenFLUID.getObserverParam
```

Returns an observer parameter value

Description

Returns an observer parameter value

Usage

```
OpenFLUID.getObserverParam(ofblob, obsid, paramname)
```

Arguments

| | |
|-----------|--------------------------------|
| ofblob | the simulation definition blob |
| obsid | the observer ID |
| paramname | the name of the parameter |

Value

the parameter value

See Also

OpenFLUID.setObserverParam
OpenFLUID.removeObserverParam

Examples

```
## Not run:  
val = OpenFLUID.getObserverParam(ofsim, "my.observer", "value")  
  
## End(Not run)
```

OpenFLUID.getObserversPaths
Returns the paths to search for observers

Description

Returns the paths to search for observers

Usage

```
OpenFLUID.getObserversPaths()
```

Value

a vector of paths

See Also

OpenFLUID.addExtraObserversPaths
OpenFLUID.getExtraObserversPaths
OpenFLUID.resetExtraObserversPaths

Examples

```
## Not run:  
paths = OpenFLUID.getObserversPaths()  
  
## End(Not run)
```

OpenFLUID.getPeriodBeginDate

Returns the simulation period begin date

Description

Returns the simulation period begin date

Usage

```
OpenFLUID.getPeriodBeginDate(ofblob)
```

Arguments

ofblob the simulation definition blob

Value

the begin date as an ISO datetime string (%Y-%m-%d %H:%M:%S)

See Also

OpenFLUID.setPeriodBeginDate

OpenFLUID.getPeriodEndDate

OpenFLUID.setPeriodEndDate

Examples

```
## Not run:  
bdate = OpenFLUID.getPeriodBeginDate(ofsim)  
  
## End(Not run)
```

OpenFLUID.getPeriodEndDate

Returns the simulation period end date

Description

Returns the simulation period end date

Usage

```
OpenFLUID.getPeriodEndDate(ofblob)
```

Arguments

ofblob the simulation definition blob

Value

the end date as an ISO datetime string (%Y-%m-%d %H:%M:%S)

See Also

OpenFLUID.setPeriodEndDate

OpenFLUID.getPeriodBeginDate

OpenFLUID.setPeriodBeginDate

Examples

```
## Not run:  
edate = OpenFLUID.getPeriodEndDate(ofsim)  
  
## End(Not run)
```

OpenFLUID.getSimulatorParam

Returns a simulator parameter value

Description

Returns a simulator parameter value

Usage

```
OpenFLUID.getSimulatorParam(ofblob, simid, paramname)
```

Arguments

| | |
|-----------|--------------------------------|
| ofblob | the simulation definition blob |
| simid | the simulator ID |
| paramname | the name of the parameter |

Value

the parameter value

See Also

OpenFLUID.setSimulatorParam
OpenFLUID.removeSimulatorParam

Examples

```
## Not run:  
val = OpenFLUID.getSimulatorParam(ofsim, "my.simulator", "coeff")  
  
## End(Not run)
```

OpenFLUID.getSimulatorsPaths
Returns the paths to search for simulators

Description

Returns the paths to search for simulators

Usage

```
OpenFLUID.getSimulatorsPaths()
```

Value

a vector of paths

See Also

OpenFLUID.addExtraSimulatorsPaths
OpenFLUID.getExtraSimulatorsPaths
OpenFLUID.resetExtraSimulatorsPaths

Examples

```
## Not run:  
paths = OpenFLUID.getSimulatorsPaths()  
  
## End(Not run)
```

```
OpenFLUID.getUnitsClasses
```

Returns the existing units classes

Description

Returns the existing units classes

Usage

```
OpenFLUID.getUnitsClasses(ofblob)
```

Arguments

ofblob the simulation definition blob

Value

a vector of units classes

See Also

```
OpenFLUID.getUnitsIDs
```

Examples

```
## Not run:  
cls = OpenFLUID.getUnitsClasses(ofsim)  
  
## End(Not run)
```

`OpenFLUID.getUnitsIDs`*Returns the existing units IDs for a given units class*

Description

Returns the existing units IDs for a given units class

Usage

```
OpenFLUID.getUnitsIDs(ofblob, unitclass)
```

Arguments

| | |
|------------------------|--------------------------------|
| <code>ofblob</code> | the simulation definition blob |
| <code>unitclass</code> | the units class |

Value

a vector of units IDs

See Also

`OpenFLUID.getUnitsClasses`

Examples

```
## Not run:
ids = OpenFLUID.getUnitsIDs(ofsim, "SU")

## End(Not run)
```

`OpenFLUID.getVersion`*Returns the OpenFLUID version*

Description

Returns the OpenFLUID version

Usage

```
OpenFLUID.getVersion()
```

Value

the OpenFLUID version number

Examples

```
## Not run:  
v = OpenFLUID.getVersion()  
  
## End(Not run)
```

OpenFLUID.loadResult

Loads results as a dataframe, giving dataset informations

Description

Loads results as a dataframe, giving dataset informations

Usage

```
OpenFLUID.loadResult(ofblob, unitclass, unitid, varname)
```

Arguments

| | |
|-----------|--------------------------------|
| ofblob | the simulation definition blob |
| unitclass | the unit class |
| unitid | the unit ID |
| varname | the variable name |

Value

a dataframe containing the simulation results

See Also

OpenFLUID.loadResultFile

Examples

```
## Not run:  
resSU18 = OpenFLUID.loadResult(ofsim, "SU", 18, "runoff")  
resRS1 = OpenFLUID.loadResult(ofsim, "RS", 1, "waterlevel")  
  
## End(Not run)
```

```
OpenFLUID.loadResultFile
```

Loads results as a dataframe, giving output file name

Description

Loads results as a dataframe, giving output file name

Usage

```
OpenFLUID.loadResultFile(filepath)
```

Arguments

filepath the full path of file to load

Value

a dataframe containing the simulation results

See Also

```
OpenFLUID.loadResult
```

Examples

```
## Not run:
resSU18 = OpenFLUID.loadResultFile("/path/to/output/SU18_full.out")
resRS1 = OpenFLUID.loadResultFile("/path/to/output/RS1_waterlevel.out")

## End(Not run)
```

```
OpenFLUID.openDataset
```

Opens a dataset and returns a simulation definition blob

Description

Opens a dataset and returns a simulation definition blob

Usage

```
OpenFLUID.openDataset(path)
```

Arguments

path the full path of the dataset to open

Value

a simulation definition blob

See Also

OpenFLUID.openProject
OpenFLUID.runSimulation

Examples

```
## Not run:  
ofsim = OpenFLUID.openDataset("/path/to/dataset")  
  
## End(Not run)
```

OpenFLUID.openProject

Opens a project and returns a simulation definition blob

Description

Opens a project and returns a simulation definition blob

Usage

```
OpenFLUID.openProject(path)
```

Arguments

path the full project to open

Value

a simulation definition blob

See Also

OpenFLUID.openDataset
OpenFLUID.runProject

Examples

```
## Not run:  
ofsim = OpenFLUID.openProject("/path/to/project")  
  
## End(Not run)
```

```
OpenFLUID.printSimulationInfo
```

Prints informations to screen about simulation definition blob

Description

Prints informations to screen about simulation definition blob

Usage

```
OpenFLUID.printSimulationInfo(ofblob)
```

Arguments

ofblob the simulation definition blob

Examples

```
## Not run:  
OpenFLUID.printSimulationInfo(ofsim)  
  
## End(Not run)
```

```
OpenFLUID.removeAttribute
```

Removes an attribute value for a given spatial unit

Description

Removes an attribute value for a given spatial unit

Usage

```
OpenFLUID.removeAttribute(ofblob, unitclass, attrname)
```

Arguments

ofblob the simulation definition blob
unitclass the unit class
attrname the name of the attribute

See Also

```
OpenFLUID.createAttribute  
OpenFLUID.getAttribute  
OpenFLUID.setAttribute
```

Examples

```
## Not run:  
OpenFLUID.removeAttribute(ofsim, "SU", "length")  
  
## End(Not run)
```

```
OpenFLUID.removeModelGlobalParam  
Removes a model global parameter value
```

Description

Removes a model global parameter value

Usage

```
OpenFLUID.removeModelGlobalParam(ofblob, paramname)
```

Arguments

| | |
|-----------|--------------------------------|
| ofblob | the simulation definition blob |
| paramname | the name of the parameter |

See Also

```
OpenFLUID.getModelGlobalParam  
OpenFLUID.setModelGlobalParam
```

Examples

```
## Not run:  
OpenFLUID.removeModelGlobalParam(ofsim, "gvalue")  
  
## End(Not run)
```

```
OpenFLUID.removeObserverParam
```

Removes a observer parameter

Description

Removes a observer parameter

Usage

```
OpenFLUID.removeObserverParam(ofblob, obsid, paramname)
```

Arguments

| | |
|-----------|--------------------------------|
| ofblob | the simulation definition blob |
| obsid | the simulation observer id |
| paramname | the name of the parameter |

See Also

```
OpenFLUID.getObserverParam  
OpenFLUID.setObserverParam
```

Examples

```
## Not run:  
OpenFLUID.removeObserverParam(ofsim, "my.observer", "value")  
  
## End (Not run)
```

```
OpenFLUID.removeSimulatorParam
```

Removes a simulator parameter

Description

Removes a simulator parameter

Usage

```
OpenFLUID.removeSimulatorParam(ofblob, simid, paramname)
```

Arguments

| | |
|-----------|--------------------------------|
| ofblob | the simulation definition blob |
| simid | the simulation simulator id |
| paramname | the name of the parameter |

See Also

OpenFLUID.getSimulatorParam
OpenFLUID.setSimulatorParam

Examples

```
## Not run:  
OpenFLUID.removeSimulatorParam(ofsim, "my.simulator", "coeff")  
  
## End (Not run)
```

OpenFLUID.resetExtraObserversPaths

Resets list of added paths to search for observers

Description

Resets list of added paths to search for observers

Usage

```
OpenFLUID.resetExtraObserversPaths ()
```

See Also

OpenFLUID.addExtraObserversPaths
OpenFLUID.getObserversPaths
OpenFLUID.getExtraObserversPaths

Examples

```
## Not run:  
OpenFLUID.resetExtraObserversPaths ()  
  
## End (Not run)
```

```
OpenFLUID.resetExtraSimulatorsPaths
```

Resets list of added paths to search for simulators

Description

Resets list of added paths to search for simulators

Usage

```
OpenFLUID.resetExtraSimulatorsPaths ()
```

See Also

```
OpenFLUID.addExtraSimulatorsPaths
```

```
OpenFLUID.getSimulatorsPaths
```

```
OpenFLUID.getExtraSimulatorsPaths
```

Examples

```
## Not run:  
OpenFLUID.resetExtraSimulatorsPaths ()  
  
## End (Not run)
```

```
OpenFLUID.runProject
```

Runs a project and returns a simulation definition blob

Description

Runs a project and returns a simulation definition blob

Usage

```
OpenFLUID.runProject (path)
```

Arguments

path the full path of the dataset to open

Value

a simulation definition blob

See Also

OpenFLUID.runSimulation

OpenFLUID.openProject

Examples

```
## Not run:
ofsim = OpenFLUID.runProject("/path/to/dataset")

## End(Not run)
```

OpenFLUID.runSimulation

Runs a simulation from a simulation definition blob

Description

Runs a simulation from a simulation definition blob

Usage

```
OpenFLUID.runSimulation(ofblob)
```

Arguments

ofblob the simulation definition blob

See Also

OpenFLUID.runProject

OpenFLUID.openProject

OpenFLUID.openDataset

Examples

```
## Not run:
OpenFLUID.runSimulation(ofsim)

## End(Not run)
```

`OpenFLUID.setAttribute`*Sets an attribute value for a given spatial unit*

Description

Sets an attribute value for a given spatial unit

Usage

```
OpenFLUID.setAttribute(ofblob, unitclass, unitid, attrname, attrval)
```

Arguments

| | |
|------------------------|--------------------------------|
| <code>ofblob</code> | the simulation definition blob |
| <code>unitclass</code> | the unit class |
| <code>unitid</code> | the unit ID |
| <code>attrname</code> | the name of the attribute |
| <code>attrval</code> | the value of the attribute |

See Also`OpenFLUID.createAttribute``OpenFLUID.getAttribute``OpenFLUID.removeAttribute`**Examples**

```
## Not run:  
OpenFLUID.setAttribute(ofsim,"SU",18,"length",12.3)  
OpenFLUID.setAttribute(ofsim,"SU",18,"CODE","ABC")  
  
## End(Not run)
```

```
OpenFLUID.setCurrentOutputDir
```

Sets the current output directory for simulations

Description

Sets the current output directory for simulations

Usage

```
OpenFLUID.setCurrentOutputDir(path)
```

Arguments

path the output directory path

Examples

```
## Not run:  
OpenFLUID.setCurrentOutputDir("/path/to/output")  
  
## End (Not run)
```

```
OpenFLUID.setDefaultDeltaT
```

Sets the simulation time step

Description

Sets the simulation time step

Usage

```
OpenFLUID.setDefaultDeltaT(ofblob, deltat)
```

Arguments

ofblob the simulation definition blob
deltat the time step value in seconds

See Also

```
OpenFLUID.getDefaultDeltaT
```

Examples

```
## Not run:
OpenFLUID.setDefaultDeltaT(60)
OpenFLUID.setDefaultDeltaT(86400)

## End(Not run)
```

OpenFLUID.setGeneratorParam

Sets a generator parameter value

Description

Sets a generator parameter value

Usage

```
OpenFLUID.setGeneratorParam(ofblob, unitclass, varname, paramname, paramval)
```

Arguments

| | |
|-----------|---|
| ofblob | the simulation definition blob |
| unitclass | the unit class to which the generator is applied |
| varname | the variable name to which the generator is applied |
| paramname | the name of the parameter |
| paramval | the value of the parameter |

See Also

OpenFLUID.getGeneratorParam

Examples

```
## Not run:
OpenFLUID.setGeneratorParam(ofsim, "SU", "var.flux", "fixedvalue", 12.3)

## End(Not run)
```

OpenFLUID.setModelGlobalParam

Sets a model global parameter value

Description

Sets a model global parameter value

Usage

```
OpenFLUID.setModelGlobalParam(ofblob, paramname, paramval)
```

Arguments

| | |
|-----------|--------------------------------|
| ofblob | the simulation definition blob |
| paramname | the name of the parameter |
| paramval | the value of the parameter |

See Also

OpenFLUID.getModelGlobalParam

OpenFLUID.removeModelGlobalParam

Examples

```
## Not run:  
OpenFLUID.setModelGlobalParam(ofsim, "gvalue", 37.2)  
  
## End(Not run)
```

OpenFLUID.setObserverParam

Sets an observer parameter value

Description

Sets an observer parameter value

Usage

```
OpenFLUID.setObserverParam(ofblob, obsid, paramname, paramval)
```

Arguments

| | |
|-----------|--------------------------------|
| ofblob | the simulation definition blob |
| obsid | the simulation observer id |
| paramname | the name of the parameter |
| paramval | the parameter value |

See Also

OpenFLUID.getObserverParam
 OpenFLUID.removeObserverParam

Examples

```
## Not run:
OpenFLUID.setObserverParam(ofsim, "my.observer", "value", 3)

## End(Not run)
```

```
OpenFLUID.setPeriodBeginDate
Sets the simulation period begin date
```

Description

Sets the simulation period begin date

Usage

```
OpenFLUID.setPeriodBeginDate(ofblob, begindate)
```

Arguments

| | |
|-----------|--|
| ofblob | the simulation definition blob |
| begindate | the begin date as an ISO datetime string (%Y-%m-%d %H:%M:%S) |

See Also

OpenFLUID.getPeriodBeginDate
 OpenFLUID.setPeriodEndDate
 OpenFLUID.getPeriodEndDate

Examples

```
## Not run:
OpenFLUID.setPeriodBeginDate(ofsim, "1997-06-05 04:00:00")

## End(Not run)
```

OpenFLUID.setPeriodEndDate
Sets the simulation period end date

Description

Sets the simulation period end date

Usage

```
OpenFLUID.setPeriodEndDate(ofblob, enddate)
```

Arguments

| | |
|---------|--|
| ofblob | the simulation definition blob |
| enddate | the end date as an ISO datetime string (%Y-%m-%d %H:%M:%S) |

See Also

```
OpenFLUID.getPeriodEndDate
OpenFLUID.setPeriodBeginDate
OpenFLUID.getPeriodBeginDate
```

Examples

```
## Not run:
OpenFLUID.setPeriodEndDate(ofsim, "1997-06-05 16:07:17")

## End(Not run)
```

```
OpenFLUID.setSimulatorParam
```

Sets a simulator parameter value

Description

Sets a simulator parameter value

Usage

```
OpenFLUID.setSimulatorParam(ofblob, simid, paramname, paramval)
```

Arguments

| | |
|-----------|--------------------------------|
| ofblob | the simulation definition blob |
| simid | the simulation simulator id |
| paramname | the name of the parameter |
| paramval | the parameter value |

See Also

```
OpenFLUID.getSimulatorParam
```

```
OpenFLUID.removeSimulatorParam
```

Examples

```
## Not run:  
OpenFLUID.setSimulatorParam(ofsim, "my.simulator", "coeff", 3)  
  
## End(Not run)
```

```
ROpenFLUID
```

Package for using OpenFLUID within the GNU R environment

Description

ROpenFLUID is a collection of functions to load, parameterize, run and analyze OpenFLUID simulations within the GNU R environment.

Details

Package: ROpenFLUID
Type: Package
Version:
Date:
License: GPLv3 with special exception
LazyLoad: yes

Author(s)

Jean-Christophe Fabre <fabrejc@supagro.inra.fr>

Examples

```
## Not run:  
# load OpenFLUID library  
library("ROpenFLUID")  
  
# add optional paths to search for simulators  
OpenFLUID.addExtraSimulatorsPaths("/path/to/simulators")  
  
# open an input dataset  
ofsim = OpenFLUID.openDataset("/path/to/dataset")  
  
# set the output dir  
OpenFLUID.setCurrentOutputDir("/path/to/output")  
  
# run the simulation  
OpenFLUID.runSimulation(ofsim)  
  
## End(Not run)
```